

# 201.CS2222-4S

## CHARGING CABLE

T2 20A 3P - T2 20A 3P 5G2,5+1x0,5mm<sup>2</sup> 4m  
SPIRAL 11kW



Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	LIBERA Series	EN 62196-1 (2014)	[European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 1: Charging of electric vehicles up to 250 A a.c. and 400 A d.c.
Product type	CHARGING CABLE		
Synthetical description	CHARGING CABLE	EN 62196-2 (2017)	[European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 2: Dimensional interchangeability requirements for a.c. pin and contact-tube accessories
Protection degree IP	IP44		
Rated current	20A	EN 50620 (2017)	[European Standard] Electric cables - Charging cables for electric vehicles
Rated voltage	400V	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Max power	11kW		
Material	THERMOPLASTIC		
Notes	T2 20A 3P - T2 20A 3P		
EV standard	Type 2 3P+N+E 16A 400V~ 11kW		
EV plug	Type 2 3P+N+E 20A 400V~		
EV connector	Type 2 3P+N+E 20A 400V~		
Cable	SPIRAL		
Cable section	5G2,5+1x0,5mm <sup>2</sup>		
Cable length	4m		
Working temperature	-30°C/+50°C		