## **Product Technical Sheet**

22 Aug 2023 21:15





## **201.CS2323-4S**CHARGING CABLE

T2 32A 1P - T2 32A 1P 3G6+1x0,5mm<sup>2</sup> 4m SPIRAL 7,4kW

**Product Approvals** 

TECHDATA		STANDARDS AND LAWS	
Commercial series	LIBERA Series	and v of ele electr	[European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 1: Charging of electric vehicles up to 250 A a.c. and 400 A d.c.
Product type	CHARGING CABLE		
Synthetical description	CHARGING CABLE	EN 62196-2 (2017) [European Standard] Plugs, and vehicle couplers. Condu of electric vehicles. Part 2: I interchangeability requirement and contact-tube accessories	[European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 2: Dimensional interchangeability requirements for a.c. pin
Protection degree IP	IP44		
Rated current	32A		and contact-tube accessories [European Standard] Electric cables -
Rated voltage	230V	, ,	Charging cables for electric vehicles [European Directives] Low Voltage Directive
Max power	7,4kW		
Material	THERMOPLASTIC		
Notes	T2 32A 1P - T2 32A 1P		
EV standard	Type 2 1P+N+E 32A 230V~ 7,4kW		
EV plug	Type 2 1P+N+E 32A 230V~		
EV connector	Type 2 1P+N+E 32A 230V~		
Cable	SPIRAL		
Cable section	3G6+1x0,5mm²		
Cable length	4m		
Working temperature	-30°C/+50°C		