



204.CA11D-UN

PILLAR CA 1 SOCKET WITH LOCK

DE 2P+E 16A 230V~ 3,7kW 16A 230V 1P+N+E
IP54 IK10

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Product type	PILLAR CA 1 SOCKET WITH LOCK	EN 61439-3 (2012-04)	[European Standard] Low-voltage switchgear and controlgear assemblies - Part 3: Distribution boards intended to be operated by ordinary persons (DBO)
Commercial series	LIBERA Series	DIRECTIVE LOW VOLTAGE 2014/35/UE	[European Directives] Low Voltage Directive
Synthetical description	PILLAR CA 1 SOCKET WITH LOCK	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Material	VARNISHED METAL		
EV standard	DE 2P+E 16A 230V~ 3,7kW		
Rated current	16A		
Rated voltage	230V		
Working frequency	50/60Hz		
Poles	1P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
Protection degree IK	IK10		
Colour	GREY		
Saline solution	Resistant		
UV protection	UV resistant		
Mounting version	ON TURRET		
Dimensions	385x1510x263mm		
HMI (Human-Machine			

Interfaces)	LCD 2x20 char
User authentication	RFID authentication
EV functions	WRK IN MODE STD-AL. FREE/PERS.
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT
EV functions	EN. MET. AND CURRENT CONSUMP.
EV functions	IDENTIF. OF AUTHORIZED USER
EV functions	MAN. OF LID LOCK. & LATCH. SYS
EV functions	CHARGE MAN. IN CASE OF PWR OUT
EV functions	PREDISP. FOR SERIAL COMMUN.
EV equipment	1 BASE WITH SEPARATION CHAMBER
EV equipment	1 COUPLE FRONT PAN. IN POLYC.
EV equipment	1 LIGHT.HEAD TRANSL. & RGB LED
EV equipment	1 FUSE HOLDER 1P+N GG 4A
EV equipment	1 DIGIT. ENERGY METER 1P+N 40A
EV equipment	1 BACKUP BATTERY
EV equipment	1 STOP CHARGE P.BTN (M. FREE)
EV equipment	1 READER RFID 13,56MHZ
EV equipment	1 LCD DISP. 2X20 ROWS BCKLIGHT
EV equipment	1 CONTROL CARD
EV equipment	1 POWER SUPPLY 24VDC 36W
EV equipment	1 MOD. CONTACT. 2P 25A 24VDC
EV equipment	1 TERMINAL STRIP 3X35MM ²
EV excluded	UPSTREAM PROTECTI. (BY INST.)

EV excluded	1 CI.BRK. 1P+N D20 30MA IST. A
EV specifications	204.CA11D-UN