## **Product Technical Sheet**

22 Aug 2023 21:24





## **204.CA21B-T2T2A**PILLAR CA 2 SOCKETS WITH LOCK

Type 2 1P+N+E 32A 230V~ 7,4kW 32A 400V 3P+N+E IP54 IK10

**Product Approvals** 

| TECHDATA                |                                  | STANDARDS  | AND LAWS  |
|-------------------------|----------------------------------|--|---|
| Product type            | PILLAR CA 2 SOCKETS<br>WITH LOCK | IEC 61439-7 (2018)   | switchgear and controlgear assemblies - Part 7: Assemblies for specific                         |
| Commercial series       | LIBERA Series                    |  | applications such as marinas, camping sites, market squares, electric vehicle charging stations |
| Version                 | PRO                              | EN IEC 61851-1<br>(2019)   | [European Standard] Electric vehicle conductive charging system - Part 1:                       |
| Synthetical description | PILLAR CA 2 SOCKETS<br>WITH LOCK | General requirements  DIRECTIVE LOW [European Directives] Low Voltage  VOLTAGE 2014/35   Directive | General requirements  |
| Material                | VARNISHED METAL                  |  |   |
| EV standard             | Type 2 1P+N+E 32A 230V~<br>7,4kW | DIRECTIVE EMC<br>2014/30/UE  | [European Directives] Electromagnetic Compatibility Directive                                   |
| Rated current           | 32A                              |  |   |
| Rated voltage           | 400V                             |  |   |
| Working frequency       | 50/60Hz                          |  |   |
| Poles                   | 3P+N+E                           |  |   |
| Protection degree IP    | IP54                             |  |   |
| Working temperature     | -30°C/+50°C                      |  |   |
| Protection degree IK    | IK10                             |  |   |
| Colour                  | GREY                             |  |   |
| Saline solution         | Resistant                        |  |   |
| UV protection           | UV resistant                     |  |   |
| Mounting version        | ON TURRET                        |  |   |
|                         |                                  |  |   |

| Dimensions                        | 385x1510x263mm                          |  |
|-----------------------------------|---|--|
| HMI (Human-Machine<br>Interfaces) | LCD 2x20 char                           |  |
| User authentication               | RFID authentication                     |  |
| Connectivity                      | Ethernet                                |  |
| Communication protocol            | OCPP 1.6 JSON                           |  |
| EV functions                      | EN. MET. AND CURRENT CONSUMP.           |  |
| EV functions                      | PR. AGAI.DIR.CON.SF.<br>CHILD SHUT      |  |
| EV functions                      | PR. AGAIN.OVERCUR. & EL. SHOCK          |  |
| EV functions                      | ID. OF CONNECTED CORD-<br>SET SIZE      |  |
| EV functions                      | CHARGE MODE 3 WITH PWM C.PILOT          |  |
| EV functions                      | WRK IN MODE STD-AL. FREE/PERS.          |  |
| EV functions                      | INTERF. WITH OCPP<br>CENTR. STAT.       |  |
| EV functions                      | CHARGE MAN. IN CASE<br>OF PWR OUT       |  |
| EV functions                      | MAN. OF LID LOCK. & LATCH. SYS          |  |
| EV functions                      | IDENTIF. OF AUTHORIZED USER             |  |
| EV functions                      | PREDISP. FOR SERIAL COMMUN.             |  |
| EV equipment                      | 2 STOP CHARGE P.BTN<br>(M. FREE)        |  |
| EV equipment                      | 1 BASE WITH<br>SEPARATION CHAMBER       |  |
| EV equipment                      | 1 LIGHT.HEAD TRANSL. & RGB LED          |  |
| EV equipment                      | 1 COUPLE FRONT PAN. IN POLYC.           |  |
| EV equipment                      | 1 TERMINAL STRIP<br>5X35MM <sup>2</sup> |  |
| EV equipment                      | 1 MAIN SWITCH 4P 40A                    |  |
| EV equipment                      | 2 CI.BRK. 1P+N C40 30MA<br>IST. A       |  |
|                                   |   |  |

| EV equipment | 1 FUSE HOLDER 1P+N GG<br>4A       |  |
|--------------|-----------------------------------|--|
| EV equipment | 2 DIGITAL ENERGY MET.<br>1P+N 40A |  |
| EV equipment | 1 BACKUP BATTERY                  |  |
| EV equipment | 1 L.SER.WIR. W. OCPP 1.6<br>J PR. |  |
| EV equipment | 2 READERS RFID 13,56MHZ           |  |
| EV equipment | 2 LCD DISP. 2X20 ROWS<br>BCKLIGHT |  |
| EV equipment | 2 CONTROL CARDS                   |  |
| EV equipment | 1 POWER SUPPLY 24VDC<br>36W       |  |
| EV equipment | 2 DC LEAKAGE<br>DETECTORS         |  |
| EV equipment | 2 MOD. CONTACT. 2P 40A 24VDC      |  |