## **Product Technical Sheet**

22 Aug 2023 21:24





## 204.CA21B-T2T2E PILLAR CA 2 SOCKETS WITH LOCK

Type 2 1P+N+E 32A 230V~ 7,4kW 32A 400V 3P+N+E IP54 IK10

**Product Approvals** 

TECHDATA		STANDARDS	
Product type	PILLAR CA 2 SOCKETS WITH LOCK	IEC 61439-7 (2018)	switchgear and controlgear assemblies - Part 7: Assemblies for specific
Commercial series	LIBERA Series		applications such as marinas, camping sites, market squares, electric vehicle charging stations
Version	PRO	EN IEC 61851-1	[European Standard] Electric vehicle
Synthetical description	PILLAR CA 2 SOCKETS WITH LOCK	(2019)	conductive charging system - Part 1: General requirements
Material	VARNISHED METAL	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
EV standard	Type 2 1P+N+E 32A 230V~ 7,4kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Rated current	32A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
Protection degree IK	IK10		
Colour	GREY		
Saline solution	Resistant		
UV protection	UV resistant		
Mounting version	ON TURRET		

Dimensions	385x1510x263mm	
HMI (Human-Machine Interfaces)	LCD 2x20 char	
User authentication	RFID authentication	
Connectivity	WiFi	
Connectivity	GSM	
Connectivity	Ethernet	
Communication protocol	OCPP 1.6 JSON	
EV functions	MAN. OF LID LOCK. & LATCH. SYS	
EV functions	WRK IN MODE STD-AL. FREE/PERS.	
EV functions	PREDISP. FOR SERIAL COMMUN.	
EV functions	INTERF. WITH OCPP CENTR. STAT.	
EV functions	WIRELESS CONNECTION TO WEB	
EV functions	CHARGE MODE 3 WITH PWM C.PILOT	
EV functions	ID. OF CONNECTED CORD- SET SIZE	
EV functions	PR. AGAIN.OVERCUR. & EL. SHOCK	
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT	
EV functions	EN. MET. AND CURRENT CONSUMP.	
EV functions	IDENTIF. OF AUTHORIZED USER	
EV functions	CHARGE MAN. IN CASE OF PWR OUT	
EV equipment	1 FUSE HOLDER 1P+N GG 4A	
EV equipment	2 DC LEAKAGE DETECTORS	
EV equipment	2 MOD. CONTACT. 2P 40A 24VDC	
EV equipment	2 CI.BRK. 1P+N C40 30MA IST. A	
	2 DIGITAL ENERGY MET.	

EV equipment	1P+N 40A
EV equipment	1 MAIN SWITCH 4P 40A
EV equipment	1 BASE WITH SEPARATION CHAMBER
EV equipment	2 STOP CHARGE P.BTN (M. FREE)
EV equipment	1 L.SER.WIR. W. OCPP 1.6 J PR.
EV equipment	1 ROUTER WI-FI/4G
EV equipment	1 TERMINAL STRIP 5X35MM <sup>2</sup>
EV equipment	1 COUPLE FRONT PAN. IN POLYC.
EV equipment	1 LIGHT.HEAD TRANSL. & RGB LED
EV equipment	1 BACKUP BATTERY
EV equipment	2 READERS RFID 13,56MHZ
EV equipment	2 LCD DISP. 2X20 ROWS BCKLIGHT
EV equipment	2 CONTROL CARDS
EV equipment	1 POWER SUPPLY 24VDC 36W