Product Technical Sheet

22 Aug 2023 21:25





204.CA21B-T2T2M PILLAR CA 2 SOCKETS WITH LOCK

Type 2 1P+N+E 32A 230V~ 7,4kW 32A 400V 3P+N+E IP54 IK10

Product Approvals

| TECHDATA | | STANDARDS | AND LAWS |
|-------------------------|----------------------------------|---|---|
| Product type | PILLAR CA 2 SOCKETS WITH LOCK | IEC 61439-7 (2018) | switchgear and controlgear assemblies - Part 7: Assemblies for specific |
| Commercial series | LIBERA Series | | applications such as marinas, camping sites, market squares, electric vehicle charging stations |
| Version | BUSINESS | EN IEC 61851-1 | [European Standard] Electric vehicle |
| Synthetical description | PILLAR CA 2 SOCKETS WITH LOCK | (2019) | conductive charging system - Part 1: General requirements |
| Material | VARNISHED METAL | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| EV standard | Type 2 1P+N+E 32A 230V~ 7,4kW | DIRECTIVE EMC 2014/30/UE | [European Directives] Electromagnetic Compatibility Directive |
| Rated current | 32A | | |
| Rated voltage | 400V | | |
| Working frequency | 50/60Hz | | |
| Poles | 3P+N+E | | |
| Protection degree IP | IP54 | | |
| Working temperature | -30°C/+50°C | | |
| Protection degree IK | IK10 | | |
| Colour | GREY | | |
| Saline solution | Resistant | | |
| UV protection | UV resistant | | |
| Mounting version | ON TURRET | | |
| | | | |

| Dimensions | 385x1510x263mm | |
|-----------------------------------|------------------------------------|--|
| HMI (Human-Machine Interfaces) | LCD 2x20 char | |
| User authentication | RFID authentication | |
| Connectivity | None | |
| EV functions | EN. MET. AND CURRENT CONSUMP. | |
| EV functions | CHARGE MODE 3 WITH PWM C.PILOT | |
| EV functions | ID. OF CONNECTED CORD- SET SIZE | |
| EV functions | PR. AGAIN.OVERCUR. & EL. SHOCK | |
| EV functions | PR. AGAI.DIR.CON.SF. CHILD SHUT | |
| EV functions | IDENTIF. OF AUTHORIZED USER | |
| EV functions | MAN. OF LID LOCK. & LATCH. SYS | |
| EV functions | CHARGE MAN. IN CASE OF PWR OUT | |
| EV functions | WRK IN MODE STD-AL. FREE/PERS. | |
| EV functions | PREDISP. FOR SERIAL COMMUN. | |
| EV equipment | 1 COUPLE FRONT PAN. IN POLYC. | |
| EV equipment | 1 LIGHT.HEAD TRANSL. & RGB LED | |
| EV equipment | 1 BASE WITH SEPARATION CHAMBER | |
| EV equipment | 2 DIG. ENER. MET. MID 1P+N 40A | |
| EV equipment | 1 BACKUP BATTERY | |
| EV equipment | 2 STOP CHARGE P.BTN (M. FREE) | |
| EV equipment | 2 READERS RFID 13,56MHZ | |
| EV equipment | 2 LCD DISP. 2X20 ROWS BCKLIGHT | |
| EV equipment | 2 CONTROL CARDS | |
| | 1 POWER SUPPLY 24VDC | |

| EV equipment | 36W |
|--------------|---|
| EV equipment | 1 FUSE HOLDER 1P+N GG 4A |
| EV equipment | 2 DC LEAKAGE DETECTORS |
| EV equipment | 2 MOD. CONTACT. 2P 40A 24VDC |
| EV equipment | 2 CI.BRK. 1P+N C40 30MA IST. A |
| EV equipment | 1 MAIN SWITCH 4P 40A |
| EV equipment | 1 TERMINAL STRIP 5X35MM ² |