



204.CA21D-T2T2ME

PILLAR CA 2 SOCKETS WITH LOCK

Type 2 1P+N+E 32A 230V~ 7,4kW 32A 400V
3P+N+E IP54 IK10

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	LIBERA Series	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Product type	PILLAR CA 2 SOCKETS WITH LOCK		
Version	PRO	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
Synthetical description	PILLAR CA 2 SOCKETS WITH LOCK	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Material	VARNISHED METAL	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
EV standard	Type 2 1P+N+E 32A 230V~ 7,4kW		
Rated current	32A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
Protection degree IK	IK10		
Colour	GREY		
Saline solution	Resistant		
UV protection	UV resistant		
Mounting version	ON TURRET		

Dimensions	385x1510x263mm
HMI (Human-Machine Interfaces)	LCD 2x20 char
User authentication	RFID authentication
Connectivity	Ethernet
Connectivity	GSM
Connectivity	WiFi
Communication protocol	OCPP 1.6 JSON
EV functions	WIRELESS CONNECTION TO WEB
EV functions	IDENTIF. OF AUTHORIZED USER
EV functions	MAN. OF LID LOCK. & LATCH. SYS
EV functions	CHARGE MAN. IN CASE OF PWR OUT
EV functions	WRK IN MODE STD-AL. FREE/PERS.
EV functions	PREDISP. FOR SERIAL COMMUN.
EV functions	INTERF. WITH OCPP CENTR. STAT.
EV functions	EN. MET. AND CURRENT CONSUMP.
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT
EV functions	ID. OF CONNECTED CORD-SET SIZE
EV functions	CHARGE MODE 3 WITH PWM C.PILOT
EV equipment	2 DIG. ENER. MET. MID 1P+N 40A
EV equipment	1 ROUTER WI-FI/4G
EV equipment	N/A
EV equipment	2 READERS RFID 13,56MHZ
EV equipment	1 BASE WITH SEPARATION CHAMBER
EV equipment	2 CONTROL CARDS
EV equipment	2 POWER SUPPLIES 24VDC 36W

EV equipment	2 FUSE HOLDERS 1P+N GG 4A
EV equipment	2 LCD DISP. 2X20 ROWS BCKLIGHT
EV equipment	2 DC LEAKAGE DETECTORS
EV equipment	2 MOD. CONTACT. 2P 40A 24VDC
EV equipment	1 TERMINAL STRIP 6X35MM ²
EV equipment	1 COUPLE FRONT PAN. IN POLYC.
EV equipment	1 LIGHT.HEAD TRANSL. & RGB LED
EV equipment	2 STOP CHARGE P.BTN (M. FREE)
EV equipment	1 L.SER.WIR. W. OCPP 1.6 J PR.
EV excluded	UPSTREAM PROTECTI. (BY INST.)
EV excluded	2 CI.BRK. 1P+N C40 30MA IST. A