Product Technical Sheet

22 Aug 2023 21:44





204.WD13F-T2WALL BOX 1 SOCKET WITH LOCK

Type 2 3P+N+E 32A 400V~ 22kW 32A 400V 3P+N+E IP54 IK10

Product Approvals

TECHDATA		STANDARDS	AND LAWS
Product type	WALL BOX 1 SOCKET WITH LOCK	IEC 61439-7 (2018) [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific	
Commercial series	LIBERA Series		applications such as marinas, camping sites, market squares, electric vehicle charging stations
Version	BUSINESS	EN IEC 61851-1 [European Standard] Electric vehicle (2019) conductive charging system - Part General requirements	[European Standard] Electric vehicle
Synthetical description	WALL BOX 1 SOCKET WITH LOCK		General requirements [European Directives] Low Voltage
Material	ENGINEERING PLASTIC		Directive
EV standard	Type 2 3P+N+E 32A 400V~ 22kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Rated current	32A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK10		
Colour	GREY		
Saline solution	Resistant		
UV protection	UV resistant		

Mounting version	SURFACE MOUNTING	
Dimensions	360x780x264mm	
HMI (Human-Machine Interfaces)	LCD 2x20 char	
User authentication	RFID authentication	
Connectivity	None	
EV functions	MAN. OF LID LOCK. & LATCH. SYS	
EV functions	CHARGE MODE 3 WITH PWM C.PILOT	
EV functions	ID. OF CONNECTED CORD- SET SIZE	
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT	
EV functions	CURRENT CONSUPTION METERING	
EV functions	IDENTIF. OF AUTHORIZED USER	
EV functions	CHARGE MAN. IN CASE OF PWR OUT	
EV functions	WRK IN MODE STD-AL. FREE/PERS.	
EV functions	PREDISP. FOR SERIAL COMMUN.	
EV equipment	1 LCD DISP. 2X20 ROWS BCKLIGHT	
EV equipment	1 CONTROL CARD	
EV equipment	1 POWER SUPPLY 24VDC 36W	
EV equipment	1 BACKUP BATTERY	
EV equipment	1 DC LEAKAGE DETECTOR	
EV equipment	1 MOD. CONTACT. 4P 40A 24VDC	
EV equipment	1 READER RFID 13,56MHZ	
EV equipment	1 FUSE HOLDER 1P+N GG 4A	
EV equipment	1 CURRENT TRANSFORMER	
EV equipment	1 TERMINAL STRIP 5X35MM ²	

EV equipment	1 LIGHTING BAR WITH RGB LED
EV equipment	1 STOP CHARGE P.BTN (M. FREE)
EV excluded	UPSTREAM PROTECTI. (BY INST.)
EV excluded	1 CI.BRK. 3P+N C40 30MA IST. A