Product Technical Sheet

22 Aug 2023 21:47





204.WD21P-T2T2WALL BOX 2 SOCKETS WITH LOCK

Type 2 1P+N+E 32A 230V~ 7,4kW 32A 400V 3P+N+E IP54 IK10

Product Approvals

TECHDATA		STANDARDS	AND LAWS
Commercial series	LIBERA Series	IEC 61439-7 (2018) [International Standard] Low-voltage switchgear and controlgear assemblies	
Product type	WALL BOX 2 SOCKETS WITH LOCK		Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Version	LITE	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1:
Synthetical description	WALL BOX 2 SOCKETS WITH LOCK	DIRECTIVE LOW	General requirements [European Directives] Low Voltage
Material	ENGINEERING PLASTIC	VOLTAGE 2014/35 Directive /UE	
EV standard	Type 2 1P+N+E 32A 230V~ 7,4kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Rated current	32A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK10		
Colour	GREY		
Saline solution	Resistant		
UV protection	UV resistant		

Mounting version	SURFACE MOUNTING	
Dimensions	360x780x264mm	
HMI (Human-Machine Interfaces)	LCD 2x20 char	
EV functions	MAN. OF LID LOCK. & LATCH. SYS	
EV functions	PR. AGAIN.OVERCUR. & EL. SHOCK	
EV functions	CHARGE MODE 3 WITH PWM C.PILOT	
EV functions	ID. OF CONNECTED CORD- SET SIZE	
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT	
EV functions	CURRENT CONSUPTION METERING	
EV functions	CHARGE MAN. IN CASE OF PWR OUT	
EV functions	WORKING IN MODE STD- ALONE FREE	
EV functions	PREDISP. FOR SERIAL COMMUN.	
EV equipment	2 DC LEAKAGE DETECTORS	
EV equipment	1 FUSE HOLDER 1P+N GG 4A	
EV equipment	1 BACKUP BATTERY	
EV equipment	2 STOP CHARGE P.BTN (M. FREE)	
EV equipment	2 LCD DISP. 2X20 ROWS BCKLIGHT	
EV equipment	2 CONTROL CARDS	
EV equipment	1 POWER SUPPLY 24VDC 36W	
EV equipment	2 LIGHTING BARS WITH RGB LED	
EV equipment	1 TERMINAL STRIP 1X35MM ²	
EV equipment	1 MAIN SWITCH 4P 40A	
EV equipment	2 CI.BRK. 1P+N C40 30MA IST. A	

EV equipment	2 CURRENT TRANSFORMERS	
EV equipment	2 MOD. CONTACT. 2P 40A 24VDC	