Product Technical Sheet

22 Aug 2023 21:48





204.WD23B-T2T2AWALL BOX 2 SOCKETS WITH LOCK

Type 2 3P+N+E 32A 400V~ 22kW 63A 400V 3P+N+E IP54 IK10

Product Approvals

TECHDATA		STANDARDS	AND LAWS
Product type	WALL BOX 2 SOCKETS WITH LOCK	IEC 61439-7 (2018)	switchgear and controlgear assemblies - Part 7: Assemblies for specific
Commercial series	LIBERA Series	sites, market squares, electric vehicl	applications such as marinas, camping sites, market squares, electric vehicle charging stations
Version	PRO	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1:
Synthetical description	WALL BOX 2 SOCKETS WITH LOCK	DIRECTIVE LOW	General requirements [European Directives] Low Voltage
Material	ENGINEERING PLASTIC	VOLTAGE 2014/35 Directive /UE	
EV standard	Type 2 3P+N+E 32A 400V~ 22kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Rated current	63A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK10		
Colour	GREY		
Saline solution	Resistant		
UV protection	UV resistant		

Mounting version	SURFACE MOUNTING	
Dimensions	360x780x264mm	
HMI (Human-Machine Interfaces)	LCD 2x20 char	
User authentication	RFID authentication	
Connectivity	Ethernet	
Communication protocol	OCPP 1.6 JSON	
EV functions	CHARGE MODE 3 WITH PWM C.PILOT	
EV functions	PR. AGAIN.OVERCUR. & EL. SHOCK	
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT	
EV functions	CHARGE MAN. IN CASE OF PWR OUT	
EV functions	ID. OF CONNECTED CORD- SET SIZE	
EV functions	INTERF. WITH OCPP CENTR. STAT.	
EV functions	EN. MET. AND CURRENT CONSUMP.	
EV functions	IDENTIF. OF AUTHORIZED USER	
EV functions	MAN. OF LID LOCK. & LATCH. SYS	
EV functions	WRK IN MODE STD-AL. FREE/PERS.	
EV functions	PREDISP. FOR SERIAL COMMUN.	
EV equipment	1 BACKUP BATTERY	
EV equipment	1 POWER SUPPLY 24VDC 36W	
EV equipment	1 FUSE HOLDER 1P+N GG 4A	
EV equipment	2 READERS RFID 13,56MHZ	
EV equipment	2 LIGHTING BARS WITH RGB LED	
EV equipment	2 DC LEAKAGE DETECTORS	
EV equipment	2 MOD. CONTACT. 4P 40A 24VDC	

EV equipment	2 CI.BRK. 3P+N C40 30MA IST. A
EV equipment	2 STOP CHARGE P.BTN (M. FREE)
EV equipment	1 L.SER.WIR. W. OCPP 1.6 J PR.
EV equipment	2 DIGITAL ENERGY MET. 3P+N 80A
EV equipment	2 LCD DISP. 2X20 ROWS BCKLIGHT
EV equipment	1 MAIN SWITCH 4P 80A
EV equipment	1 TERMINAL STRIP 1X35MM ²
EV equipment	2 CONTROL CARDS