SCAME

204.WD26C-T2T2

WALL BOX 2 SOCKETS WITH LOCK

Type 2 3P+N+E 32A 400V~ 22kW 32A 400V 3P+N+E IP54 IK10

Product Approvals

TECHDATA

Commercial series	LIBERA Series
Product type	WALL BOX 2 SOCKETS WITH LOCK
Version	BUSINESS
Synthetical description	WALL BOX 2 SOCKETS WITH LOCK
Material	ENGINEERING PLASTIC
EV standard	Type 2 3P+N+E 32A 400V~ 22kW
Rated current	32A
Rated voltage	400V
Working frequency	50/60Hz
Poles	3P+N+E
Protection degree IP	IP54
Working temperature	-30°C/+50°C
GLOW WIRE	GW 650°C
Protection degree IK	IK10
Colour	GREY
Saline solution	Resistant
UV protection	UV resistant

STANDARDS AND LAWS

IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
DIRECTIVE LOW VOLTAGE 2014/35/UE	[European Directives] Low Voltage Directive
DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive

Mounting version	SURFACE MOUNTING
Dimensions	360x780x264mm
HMI (Human-Machine Interfaces)	LCD 2x20 char
User authentication	RFID authentication
Connectivity	None
EV functions	CURRENT CONSUPTION METERING
EV functions	CHARGE MODE 3 WITH PWM C.PILOT
EV functions	ID. OF CONNECTED CORD-SET SIZE
EV functions	PR. AGAIN.OVERCUR. & EL. SHOCK
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT
EV functions	IDENTIF. OF AUTHORIZED USER
EV functions	MAN. OF LID LOCK. & LATCH. SYS
EV functions	CHARGE MAN. IN CASE OF PWR OUT
EV functions	WRK IN MODE STD-AL. FREE/PERS.
EV functions	PREDISP. FOR SERIAL COMMUN.
EV equipment	1 POWER SUPPLY 24VDC 36W
EV equipment	1 FUSE HOLDER 1P+N GG 4A
EV equipment	2 DC LEAKAGE DETECTORS
EV equipment	2 MOD. CONTACT. 4P 25A 24VDC
EV equipment	2 CURRENT TRANSFORMERS
EV equipment	2 CI.BRK. 3P+N C20 30MA IST. A
EV equipment	1 TERMINAL STRIP 1X35MM²
EV equipment	2 LIGHTING BARS WITH RGB LED

EV equipment	1 MAIN SWITCH 4P 40A
EV equipment	1 BACKUP BATTERY
EV equipment	2 STOP CHARGE P.BTN (M. FREE)
EV equipment	2 READERS RFID 13,56MHZ
EV equipment	2 LCD DISP. 2X20 ROWS BCKLIGHT
EV equipment	2 CONTROL CARDS