Product Technical Sheet

22 Aug 2023 21:53





205.A33-B0PILLAR BE-A

Type 2 1P+N+E 32A 230V~ 7,4kW 32A 230V 1P+N+E IP54 IK10

Product Approvals

TECHDATA		STANDARDS	AND LAWS
Commercial series	BE-A Series	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies -
Product type	PILLAR BE-A	Part 7: Assemblies for specific applications such as marinas, camping	
Version	BUSINESS	EN 150 04054 4	charging stations
Synthetical description	PILLAR BE-A	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
Material	VARNISHED METAL	DIRECTIVE LOW VOLTAGE 2014/35	[European Directives] Low Voltage Directive
EV standard	Type 2 1P+N+E 32A 230V~ 7,4kW	/UE DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Rated current	32A		
Rated voltage	230V		
Working frequency	50/60Hz		
Poles	1P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
Protection degree IK	IK10		
Colour	BRONZE		
Saline solution	Resistant		
UV protection	UV resistant		
Mounting version	ON TURRET		
Dimensions	220x1466x300mm		

HMI (Human-Machine Interfaces)	LCD 2x20 char	
User authentication	RFID authentication	
Connectivity	None	
EV functions	EN. MET. AND CURRENT CONSUMP.	
EV functions	IDENTIF. OF AUTHORIZED USER	
EV functions	MAN. OF LID LOCK. & LATCH. SYS	
EV functions	CHARGE MAN. IN CASE OF PWR OUT	
EV functions	WRK IN MODE STD-AL. FREE/PERS.	
EV functions	PREDISP. FOR SERIAL COMMUN.	
EV functions	CHARGE MODE 3 WITH PWM C.PILOT	
EV functions	ID. OF CONNECTED CORD- SET SIZE	
EV functions	PR. AGAIN.OVERCUR. & EL. SHOCK	
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT	
EV equipment	1 BACKUP BATTERY	
EV equipment	1 BASE WITH SEPARATION CHAMBER	
EV equipment	1 TERMINAL STRIP 3X35MM ²	
EV equipment	1 CI.BRK. 1P+N C40 30MA IST. A	
EV equipment	1 MOD. CONTACT. 2P 40A 24VDC	
EV equipment	1 DC LEAKAGE DETECTOR	
EV equipment	1 FUSE HOLDER 1P+N GG 4A	
EV equipment	1 POWER SUPPLY 24VDC 36W	
EV equipment	1 CONTROL CARD	
EV equipment	1 LCD DISP. 2X20 ROWS BCKLIGHT	

EV equipment	1 READER RFID 13,56MHZ
EV equipment	1 STOP CHARGE P.BTN (M. FREE)
EV equipment	1 SOCKET FR. LOC. WITH RGB LED
EV equipment	1 DIG. ENER. MET. MID 1P+N 40A
EV specifications	205.A33-B0