



205.B33-UU PILLAR BE-B

Type 2 3P+N+E 32A 400V~ 22kW 63A 400V
3P+N+E IP54 IK10 Type 2 4m SPIRAL

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	BE-B Series	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Product type	PILLAR BE-B		
Version	BUSINESS	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
Synthetical description	PILLAR BE-B		
Material	VARNISHED METAL	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
EV standard	Type 2 3P+N+E 32A 400V~ 22kW		
With integrated cable	Type 2	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Cable length	4m		
Cable section	5G6+1x0,5mm ²		
Cable	SPIRAL		
Rated current	63A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
Protection degree IK	IK10		
Colour	BRONZE		

Saline solution	Resistant
UV protection	UV resistant
Mounting version	ON TURRET
Dimensions	300x1466x300mm
HMI (Human-Machine Interfaces)	LCD 2x20 char
User authentication	RFID authentication
Connectivity	None
EV functions	CHARGE MAN. IN CASE OF PWR OUT
EV functions	CHARGE MODE 3 WITH PWM C.PILOT
EV functions	PR. AGAIN.OVERCUR. & EL. SHOCK
EV functions	EN. MET. AND CURRENT CONSUMP.
EV functions	IDENTIF. OF AUTHORIZED USER
EV functions	MAN. OF CON.LOCK. IN INLET DMY
EV functions	PWR CONTACTOR APERTURE MONIT.
EV functions	WRK IN MODE STD-AL. FREE/PERS.
EV functions	PREDISP. FOR SERIAL COMMUN.
EV equipment	1 BASE WITH SEPARATION CHAMBER
EV equipment	2 INLETS DUMMY WITH RGB LED
EV equipment	N/A
EV equipment	2 DIG. ENER. MET. MID 3P+N 80A
EV equipment	1 BACKUP BATTERY
EV equipment	2 STOP CHARGE P.BTN (M. FREE)
EV equipment	2 READERS RFID 13,56MHZ
EV equipment	2 LCD DISP. 2X20 ROWS BCKLIGHT

EV equipment	2 CONTROL CARDS
EV equipment	1 POWER SUPPLY 24VDC 36W
EV equipment	1 FUSE HOLDER 1P+N GG 4A
EV equipment	2 DC LEAKAGE DETECTORS
EV equipment	2 MOD. CONTACT. 4P 40A 24VDC
EV equipment	2 SHUNT TRIP RELEASES 24VDC
EV equipment	2 CI.BRK. 3P+N C40 30MA IST. A
EV equipment	1 MAIN SWITCH 4P 80A
EV equipment	1 TERMINAL STRIP 5X35MM ²
EV equipment	N/A
EV specifications	205.B33-UU