Product Technical Sheet

22 Aug 2023 22:04





205.EVW19-B0WALL BOX 1 SOCKET TYPE 2

Type 2 1P+N+E 32A 230V~ 7,4kW 32A 230V 1P+N+E IP54 IK08

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	BE-W Series	IEC 61851-1 (2010)	[International Standard] Electric vehicle conductive charging system - Part 1:
Product type	WALL BOX 1 SOCKET TYPE 2	IEC 61439-7 (2018)	switchgear and controlgear assemblies -
Version	SOLO	Part 7: Assemblies for specific	Part 7: Assemblies for specific applications such as marinas, camping
Synthetical description	WALL BOX 1 SOCKET TYPE 2		charging stations
Material	ENGINEERING PLASTIC		
EV standard	Type 2 1P+N+E 32A 230V~ 7,4kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Rated current	32A		
Rated voltage	230V		
Working frequency	50/60Hz		
Poles	1P+N+E		
Protection degree IP	IP54		
Working temperature	-25°C/+40°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		
Colour	ANTHRACITE		
Saline solution	Resistant		
UV protection	UV resistant		

Mounting version	SURFACE MOUNTING	
Dimensions	235x370x115mm	
Certifications	EV READY 1.4 COMPLIANT	
EV functions	WORKING IN MODE STD- ALONE FREE	
EV functions	PWR CONTACTOR APERTURE MONIT.	
EV functions	MANAGING OF LATCHING SYSTEM	
EV functions	EN. MET. AND CURRENT CONSUMP.	
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT	
EV functions	ID. OF CONNECTED CORD- SET SIZE	
EV functions	CHARGE MODE 3 WITH PWM C.PILOT	
EV equipment	1 POWER SUPPLY 24VDC 36W	
EV equipment	1 CONTROL CARD	
EV equipment	1 COUPLE OF SERVICE LED	
EV equipment	1 STOP CHARGE P.BTN (M. FREE)	
EV equipment	1 TERMINAL STRIP 3X10MM ²	
EV equipment	1 DIGIT.ENERGY METER 1P+N 45A	
EV equipment	1 IND. CONTACT. 2P 32A 24VDC	
EV equipment	1 FUSE HOLDER 1P+N GG 4A	
EV excluded	1 CI.BRK. 1P+N C40 30MA	
EV excluded	UPSTREAM PROTECTI. (BY INST.)	
EV excluded	1 CI.BRK. RCD TYPE B	
EV excluded	1 SHUNT TRIP RELEASE 24VDC	
EV excluded	EMERGENCY LINE 24VDC (OPTIONAL)	
EV specifications	205.EVW19-B0	