



# 205.W11-R0

## WALL BOX CABLE+SOCKET T2

Type 2 1P+N+E 16A 230V~ 3,7kW 16A 230V  
1P+N+E IP54 IK08 Type 2 4m

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	BE-W Series	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Product type	WALL BOX CABLE+SOCKET T2		
Version	SOLO	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
Synthetical description	WALL BOX CABLE+SOCKET T2	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Material	ENGINEERING PLASTIC	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
EV standard	Type 2 1P+N+E 16A 230V~ 3,7kW		
With integrated cable	Type 2		
Cable length	4m		
Cable section	3G2,5+1x0,5mm <sup>2</sup>		
Rated current	16A		
Rated voltage	230V		
Working frequency	50/60Hz		
Poles	1P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		

Colour	ANTHRACITE
Saline solution	Resistant
UV protection	UV resistant
Mounting version	SURFACE MOUNTING
Dimensions	235x370x115mm
Product replaced by:	205.W113-S
EV functions	WORKING IN MODE STD-ALONE FREE
EV functions	PREDISP. FOR SERIAL COMMUN.
EV functions	CHARGE MODE 3 WITH PWM C.PILOT
EV functions	PR. AGAIN.OVERCUR. & EL. SHOCK
EV functions	CURRENT CONSUPTION METERING
EV functions	PWR CONTACTOR APERTURE MONIT.
EV equipment	1 CI.BRK. 1P+N D20 30MA IST. A
EV equipment	1 CABLE HOLDER IN TECHNOPOLYM.
EV equipment	1 STOP CHARGE P.BTN (M. FREE)
EV equipment	1 MOD. CONTACT. 2P 25A 24VDC
EV equipment	1 DC LEAKAGE DETECTOR
EV equipment	1 FUSE HOLDER 1P+N GG 4A
EV equipment	1 RBG LED STRIPES
EV equipment	1 CONTROL CARD
EV equipment	1 CURRENT TRANSFORMER
EV equipment	1 POWER SUPPLY 24VDC 36W
EV equipment	1 SHUNT TRIP RELEASE 24VDC
EV equipment	1 TERMINAL STRIP 3X10MM <sup>2</sup>
	1 CABLE 3G2,5+1X0,5MM <sup>2</sup>

EV equipment	4M
EV specifications	205.W11-R0