## **Product Technical Sheet**

22 Aug 2023 22:13





## **205.W18-C0**WALL BOX 1 SOCKET TYPE 2

Type 2 3P+N+E 16A 400V~ 11kW 16A 400V 3P+N+E IP54 IK08

**Product Approvals** 

TECHDATA		STANDARDS	AND LAWS
Commercial series	BE-W Series	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Product type	WALL BOX 1 SOCKET TYPE 2	ap sit	
Version	SOLO	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1:
Synthetical description	WALL BOX 1 SOCKET TYPE 2	DIRECTIVE LOW	General requirements [European Directives] Low Voltage
Material	ENGINEERING PLASTIC	VOLTAGE 2014/35 Directive /UE	
EV standard	Type 2 3P+N+E 16A 400V~ 11kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Rated current	16A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		
Colour	ANTHRACITE		
Saline solution	Resistant		
UV protection	UV resistant		

Mounting version	SURFACE MOUNTING	
Dimensions	235x370x115mm	
Product replaced by:	205.W119-D	
HMI (Human-Machine Interfaces)	LCD 2x20 char	
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT	
EV functions	MANAGING OF LATCHING SYSTEM	
EV functions	CHARGE MAN. IN CASE OF PWR OUT	
EV functions	PREDISP. FOR SERIAL COMMUN.	
EV functions	WORKING IN MODE STD- ALONE FREE	
EV functions	CURRENT CONSUPTION METERING	
EV functions	ID. OF CONNECTED CORD- SET SIZE	
EV functions	CHARGE MODE 3 WITH PWM C.PILOT	
EV equipment	1 CURRENT TRANSFORMER	
EV equipment	1 DC LEAKAGE DETECTOR	
EV equipment	1 MOD. CONTACT. 4P 25A 24VDC	
EV equipment	1 TERMINAL STRIP 5X10MM <sup>2</sup>	
EV equipment	1 RBG LED STRIPES	
EV equipment	1 LCD DISP. 2X20 ROWS BCKLIGHT	
EV equipment	1 CONTROL CARD	
EV equipment	1 POWER SUPPLY 24VDC 36W	
EV equipment	1 FUSE HOLDER 1P+N GG 4A	
EV equipment	1 STOP CHARGE P.BTN (M. FREE)	
EV equipment	1 BACKUP BATTERY	
EV excluded	1 CI.BRK. 3P+N C20 30MA IST. A	

EV excluded	UPSTREAM PROTECTI. (BY INST.)
EV specifications	205.W18-C0