Product Technical Sheet

22 Aug 2023 22:15





205.W20-D0WALL BOX 1 SOCKET TYPE 2

Type 2 3P+N+E 32A 400V~ 22kW 32A 400V 3P+N+E IP54 IK08

Product Approvals

TECHDATA		STANDARDS	AND LAWS
Commercial series	BE-W Series	IEC 61439-7 (2018)	switchgear and controlgear assemblies -
Product type	WALL BOX 1 SOCKET TYPE 2	Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations	
Version	SOLO	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1:
Synthetical description	WALL BOX 1 SOCKET TYPE 2	DIRECTIVE LOW	General requirements [European Directives] Low Voltage
Material	ENGINEERING PLASTIC	VOLTAGE 2014/35 Directive /UE	
EV standard	Type 2 3P+N+E 32A 400V~ 22kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Rated current	32A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		
Colour	ANTHRACITE		
Saline solution	Resistant		
UV protection	UV resistant		

Mounting version	SURFACE MOUNTING	
Dimensions	235x370x115mm	
Product replaced by:	205.W119-D	
EV functions	CHARGE MODE 3 WITH PWM C.PILOT	
EV functions	ID. OF CONNECTED CORD- SET SIZE	
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT	
EV functions	CURRENT CONSUPTION METERING	
EV functions	MANAGING OF LATCHING SYSTEM	
EV functions	CHARGE MAN. IN CASE OF PWR OUT	
EV functions	WORKING IN MODE STD- ALONE FREE	
EV functions	PREDISP. FOR SERIAL COMMUN.	
EV equipment	1 TERMINAL STRIP 5X10MM ²	
EV equipment	1 MOD. CONTACT. 4P 40A 24VDC	
EV equipment	1 CURRENT TRANSFORMER	
EV equipment	1 BACKUP BATTERY	
EV equipment	1 STOP CHARGE P.BTN (M. FREE)	
EV equipment	1 RBG LED STRIPES	
EV equipment	1 CONTROL CARD	
EV equipment	1 POWER SUPPLY 24VDC 36W	
EV equipment	1 FUSE HOLDER 1P+N GG 4A	
EV excluded	UPSTREAM PROTECTI. (BY INST.)	
EV excluded	1 CI.BRK. 3P+N C40 30MA IST. B	