Product Technical Sheet

22 Aug 2023 22:18





205.W33-B0

WALL BOX 1 SOCKET TYPE 2

Type 2 1P+N+E 32A 230V~ 7,4kW 32A 230V 1P+N+E IP54 IK08

Product Approvals

TECHDATA		STANDARDS	AND LAWS
Product type	WALL BOX 1 SOCKET TYPE 2	IEC 61439-7 (2018) [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations	
Commercial series	BE-W Series		
Version	BUSINESS	EN IEC 61851-1 [European Standard] Electric vehicle (2019) [European Standard] Electric vehicle conductive charging system - Part 1: General requirements	[European Standard] Electric vehicle
Synthetical description	WALL BOX 1 SOCKET TYPE 2		
Material	ENGINEERING PLASTIC	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
EV standard	Type 2 1P+N+E 32A 230V~ 7,4kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Rated current	32A		
Rated voltage	230V		
Working frequency	50/60Hz		
Poles	1P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		
Colour	ANTHRACITE		
Saline solution	Resistant		
UV protection	UV resistant		

SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122

Mounting version	SURFACE MOUNTING	
Dimensions	235x370x115mm	
Product replaced by:	205.W33-B	
HMI (Human-Machine Interfaces)	LCD 2x20 char	
User authentication	RFID authentication	
Connectivity	None	
EV functions	PR. AGAIN.OVERCUR. & EL. SHOCK	
EV functions	CHARGE MODE 3 WITH PWM C.PILOT	
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT	
EV functions	EN. MET. AND CURRENT CONSUMP.	
EV functions	ID. OF CONNECTED CORD- SET SIZE	
EV functions	IDENTIF. OF AUTHORIZED USER	
EV functions	MANAGING OF LATCHING SYSTEM	
EV functions	CHARGE MAN. IN CASE OF PWR OUT	
EV functions	WRK IN MODE STD-AL. FREE/PERS.	
EV functions	PREDISP. FOR SERIAL COMMUN.	
EV equipment	1 LCD DISP. 2X20 ROWS BCKLIGHT	
EV equipment	1 MOD. CONTACT. 2P 40A 24VDC	
EV equipment	1 CI.BRK. 1P+N C40 30MA IST. A	
EV equipment	1 TERMINAL STRIP 3X10MM ²	
EV equipment	1 DIG. ENER. MET. MID 1P+N 40A	
EV equipment	1 CONTROL CARD	
EV equipment	1 POWER SUPPLY 24VDC 36W	
	1 FUSE HOLDER 1P+N GG	

EV equipment	4A
EV equipment	1 DC LEAKAGE DETECTOR
EV equipment	1 BACKUP BATTERY
EV equipment	1 STOP CHARGE P.BTN (M. FREE)
EV equipment	1 RBG LED STRIPES
EV equipment	1 READER RFID 13,56MHZ
EV specifications	205.W33-B0