Product Technical Sheet

22 Aug 2023 22:19





205.W35-B0WALL BOX 1 SOCKET TYPE 2

Type 2 1P+N+E 32A 230V~ 7,4kW 32A 230V 1P+N+E IP54 IK08

Product Approvals

TEOUDATA		CTANDADDO	ANDLAWO
TECHDATA		STANDARDS	
Product type	WALL BOX 1 SOCKET TYPE 2	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific
Commercial series	BE-W Series	applications such as marinas, camping sites, market squares, electric vehicle charging stations	
Version	BUSINESS	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1:
Synthetical description	WALL BOX 1 SOCKET TYPE 2	DIRECTIVE LOW	General requirements [European Directives] Low Voltage
Material	ENGINEERING PLASTIC	VOLTAGE 2014/35 /UE	Directive
EV standard	Type 2 1P+N+E 32A 230V~ 7,4kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Rated current	32A		
Rated voltage	230V		
Working frequency	50/60Hz		
Poles	1P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		
Colour	ANTHRACITE		
Saline solution	Resistant		
UV protection	UV resistant		

Mounting version	SURFACE MOUNTING	
Dimensions	235x370x115mm	
Product replaced by:	205.W36-B	
HMI (Human-Machine Interfaces)	LCD 2x20 char	
User authentication	RFID authentication	
Connectivity	None	
EV functions	CURRENT CONSUPTION METERING	
EV functions	IDENTIF. OF AUTHORIZED USER	
EV functions	MANAGING OF LATCHING SYSTEM	
EV functions	CHARGE MAN. IN CASE OF PWR OUT	
EV functions	WRK IN MODE STD-AL. FREE/PERS.	
EV functions	PREDISP. FOR SERIAL COMMUN.	
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT	
EV functions	ID. OF CONNECTED CORD- SET SIZE	
EV functions	CHARGE MODE 3 WITH PWM C.PILOT	
EV equipment	1 TERMINAL STRIP 3X10MM ²	
EV equipment	1 MOD. CONTACT. 2P 40A 24VDC	
EV equipment	1 CURRENT TRANSFORMER	
EV equipment	1 BACKUP BATTERY	
EV equipment	1 STOP CHARGE P.BTN (M. FREE)	
EV equipment	1 RBG LED STRIPES	
EV equipment	1 READER RFID 13,56MHZ	
EV equipment	1 LCD DISP. 2X20 ROWS BCKLIGHT	
EV equipment	1 CONTROL CARD	
	1 POWER SUPPLY 24VDC	

EV equipment	36W
EV equipment	1 FUSE HOLDER 1P+N GG 4A
EV equipment	1 DC LEAKAGE DETECTOR
EV excluded	UPSTREAM PROTECTI. (BY INST.)
EV excluded	1 CI.BRK. 1P+N C40 30MA IST. A