Product Technical Sheet

22 Aug 2023 22:22





205.W40-D0

WALL BOX 1 SOCKET TYPE 2

Type 2 3P+N+E 32A 400V~ 22kW 32A 400V 3P+N+E IP54 IK08

Product Approvals

TECHDATA		STANDARDS	
Commercial series	BE-W Series	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies -
Product type	WALL BOX 1 SOCKET TYPE 2		Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Version	BUSINESS	EN IEC 61851-1	[European Standard] Electric vehicle
Synthetical description	WALL BOX 1 SOCKET TYPE 2	(2019) conductive charging system - Part 1: General requirements	
Material	ENGINEERING PLASTIC	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
EV standard	Type 2 3P+N+E 32A 400V~ 22kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Rated current	32A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		
Colour	ANTHRACITE		
Saline solution	Resistant		
UV protection	UV resistant		

SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122

Mounting version	SURFACE MOUNTING	
Dimensions	235x370x115mm	
Product replaced by:	205.W36-D	
HMI (Human-Machine Interfaces)	LCD 2x20 char	
User authentication	RFID authentication	
EV functions	MANAGING OF LATCHING SYSTEM	
EV functions	CHARGE MODE 3 WITH PWM C.PILOT	
EV functions	ID. OF CONNECTED CORD- SET SIZE	
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT	
EV functions	EN. MET. AND CURRENT CONSUMP.	
EV functions	IDENTIF. OF AUTHORIZED USER	
EV functions	CHARGE MAN. IN CASE OF PWR OUT	
EV functions	WRK IN MODE STD-AL. FREE/PERS.	
EV functions	PREDISP. FOR SERIAL COMMUN.	
EV equipment	1 STOP CHARGE P.BTN (M. FREE)	
EV equipment	1 READER RFID 13,56MHZ	
EV equipment	1 RBG LED STRIPES	
EV equipment	1 DIGIT. ENERGY METER 3P+N 80A	
EV equipment	1 BACKUP BATTERY	
EV equipment	1 TERMINAL STRIP 5X10MM ²	
EV equipment	1 MOD. CONTACT. 4P 40A 24VDC	
EV equipment	1 FUSE HOLDER 1P+N GG 4A	
EV equipment	1 POWER SUPPLY 24VDC 36W	
EV equipment	1 CONTROL CARD	

EV equipment	1 LCD DISP. 2X20 ROWS BCKLIGHT
EV excluded	UPSTREAM PROTECTI. (BY INST.)
EV excluded	1 CI.BRK. 3P+N C40 30MA IST. B