

Product Technical Sheet

22 Aug 2023 22:30



205.W75-D0

WALL BOX 1 SOCKET TYPE 2

Type 2 3P+N+E 32A 400V~ 22kW 32A 400V
3P+N+E IP54 IK08

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	BE-W Series	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Product type	WALL BOX 1 SOCKET TYPE 2		
Version	PRO	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
Synthetical description	WALL BOX 1 SOCKET TYPE 2	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Material	ENGINEERING PLASTIC	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
EV standard	Type 2 3P+N+E 32A 400V~ 22kW		
Rated current	32A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		
Colour	ANTHRACITE		
Saline solution	Resistant		
UV protection	UV resistant		

Mounting version	SURFACE MOUNTING
Dimensions	235x370x115mm
Product replaced by:	205.W85-D
HMI (Human-Machine Interfaces)	LCD 2x20 char
User authentication	RFID authentication
Connectivity	Ethernet
Connectivity	GSM
Connectivity	WiFi
Communication protocol	OCPP 1.6 JSON
EV functions	PR. AGAI.DIR.CON.SF. CHILD SHUT
EV functions	CHARGE MODE 3 WITH PWM C.PILOT
EV functions	ID. OF CONNECTED CORD- SET SIZE
EV functions	EN. MET. AND CURRENT CONSUMP.
EV functions	IDENTIF. OF AUTHORIZED USER
EV functions	MANAGING OF LATCHING SYSTEM
EV functions	CHARGE MAN. IN CASE OF PWR OUT
EV functions	WRK IN MODE STD-AL. FREE/PERS.
EV functions	PREDISP. FOR SERIAL COMMUN.
EV functions	INTERF. WITH OCPP CENTR. STAT.
EV functions	WIRELESS CONNECTION TO WEB
EV equipment	1 STOP CHARGE P.BTN (M. FREE)
EV equipment	1 LCD DISP. 2X20 ROWS BCKLIGHT
EV equipment	1 READER RFID 13,56MHZ
EV equipment	1 RBG LED STRIPES
EV equipment	1 POWER SUPPLY 24VDC 36W

EV equipment	1 FUSE HOLDER 1P+N GG 4A
EV equipment	1 DC LEAKAGE DETECTOR
EV equipment	1 MOD. CONTACT. 4P 40A 24VDC
EV equipment	1 TERMINAL STRIP 5X10MM ²
EV equipment	1 ROUTER WI-FI/4G
EV equipment	1 L.SER.WIR. W. OCPP 1.6 J PR.
EV equipment	1 CONTROL CARD
EV equipment	1 DIGIT. ENERGY METER 3P+N 80A
EV equipment	1 BACKUP BATTERY
EV excluded	1 CI.BRK. 3P+N C40 30MA IST. A
EV excluded	UPSTREAM PROTECTI. (BY INST.)
EV specifications	205.W75-D0