

## Product Technical Sheet

23 Aug 2023 12:42



# 504.1674.RU

## INTERLOCKED SOCKET

16A 3P+E 9h 200-250V 50Hz 60Hz II 2GD  
130X260MM\_PAR Screw terminals With  
mechanical interlock EAC [Eurasian Conformity]

Product Approvals

TECHDATA		STANDARDS AND LAWS
Product type	INTERLOCKED SOCKET	31610.0-2014 (IEC [ ] . 60079-0)
Commercial series	ADVANCE-GRP[GD] Series	
Synthetical description	INTERLOCKED SOCKET	
Mounting version	SURFACE MOUNTING	
Rated current	16A	
Poles	3P+E	
Hour position	9h	
Rated voltage (range)	200-250V	
Rated voltage	200-250V	
Working frequency	60Hz	
Working frequency	50Hz	
Colour	BLUE	
Material	GRP Glass Reinforced Polyester	
Protection degree	Splash proof	
Protection degree IP	IP66	
Protection degree IK	IK10	
Terminals	Screw terminals	
Contact material	CuZn (brass)	

Flange	130X260MM_PAR
Cable entry	1xM25
Working temperature	-40°C/+60°C
GLOW WIRE	GW 960°C
Self-extinguishing UL94	V0
Group and categories EX	II 2GD
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	60 °C
Options	EAC [Eurasian Conformity]
Options	With mechanical interlock
Padlock	ø5mm