



504.16865-A.RU

INTERLOCKED SOCKET

16A 3P+E 11h 440-460V 60Hz II 2GD
 130X260MM_PAR Screw terminals With
 mechanical interlock EAC [Eurasian Conformity]
 Low temperature [-50°C]

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|--------------------------------|----------------------------------|--|
| Product type | INTERLOCKED SOCKET | 31610.0-2014 (IEC [] . 60079-0) | |
| Commercial series | ADVANCE-GRP[GD] Series | DIRECTIVE ATEX 2014/34/UE | [European Directives] Atmosphere Explosive |
| Synthetical description | INTERLOCKED SOCKET | | |
| Mounting version | SURFACE MOUNTING | | |
| Rated current | 16A | | |
| Poles | 3P+E | | |
| Hour position | 11h | | |
| Rated voltage (range) | 400V-up | | |
| Rated voltage | 440-460V | | |
| Working frequency | 60Hz | | |
| Colour | RED | | |
| Material | GRP Glass Reinforced Polyester | | |
| Protection degree | Splash proof | | |
| Protection degree IP | IP66 | | |
| Protection degree IK | IK10 | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |
| Flange | 130X260MM_PAR | | |

| | |
|----------------------------|---------------------------|
| Cable entry | 1xM25 |
| Working temperature | -40°C/+60°C |
| GLOW WIRE | GW 960°C |
| Self-extinguishing UL94 | V0 |
| Group and categories EX | II 2GD |
| Ambient temperature Ta min | -50 °C |
| Ambient temperature Ta max | 60 °C |
| Options | EAC [Eurasian Conformity] |
| Options | With mechanical interlock |
| Options | Low temperature [-50°C] |
| Padlock | ø5mm |