



504.16877

INTERLOCKED SOCKET

16A 3P+N+E 5h 600-690V 50Hz 60Hz II 2GD
130X260MM_PAR Screw terminals With
mechanical interlock

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ADVANCE-GRP[GD] Series	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Product type	INTERLOCKED SOCKET	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Synthetical description	INTERLOCKED SOCKET		
Mounting version	SURFACE MOUNTING		
Rated current	16A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poles	3P+N+E	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Hour position	5h		
Rated voltage (range)	400V-up	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Rated voltage	600-690V		
Working frequency	60Hz	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 1: General requirements
Working frequency	50Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Colour	RED		
Material	GRP Glass Reinforced Polyester		
Protection degree	Splash proof	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Protection degree IP	IP66	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Protection degree IK	IK10		
Terminals	Screw terminals	IEC 60079-31 (2013)	[International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Contact material	CuZn (brass)	EN 60079-1 (2014)	[European Standard] Electrical apparatus

Flange	130X260MM_PAR		for explosive gas atmospheres - Part 1: Flameproof enclosures 'd'
Cable entry	1xM25	EN 60079-7 (2015)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Working temperature	-40°C/+60°C	IEC 60079-1 (2014)	[International Standard] Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d".
GLOW WIRE	GW 960°C		
Self-extinguishing UL94	V0	IEC 60079-0 (2017)	[International Standard] Explosive atmospheres - Part 0: Equipment - General requirements
Group and categories EX	II 2GD	IEC 60079-7 (2017)	[International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e".
Ambient temperature Ta min	-35 °C		
Ambient temperature Ta max	60 °C	EN 60079-7 (2018)	[European Standard] Explosive atmospheres. - Part 7: Equipment protection by increased safety "e"
Options	With mechanical interlock	EN 60079-0 (2018)	[European Standard] Explosive atmospheres. General requirements.
Padlock	ø5mm	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive