

# 506.16875

## INTERLOCKED SOCKET

16A 3P+N+E 11h 440-460V 60Hz  
136X125MM\_PAR Screw terminals With  
mechanical interlock



Product Approvals

| TECHDATA                |                    | STANDARDS AND LAWS                |   |
|-------------------------|--------------------|-----------------------------------|---|
| Commercial series       | OMNIA Series       | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Product type            | INTERLOCKED SOCKET | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations   |
| Synthetical description | INTERLOCKED SOCKET |                                   |   |
| Mounting version        | SURFACE MOUNTING   |                                   |   |
| Rated current           | 16A                | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Poles                   | 3P+N+E             | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations   |
| Hour position           | 11h                |                                   |   |
| Rated voltage (range)   | 400V-up            | EN 60309-4 (2007)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock   |
| Rated voltage           | 440-460V           |                                   |   |
| Working frequency       | 60Hz               | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 1: General requirements  |
| Colour                  | RED                | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Material                | THERMOPLASTIC      |                                   |   |
| Protection degree       | Watertight         |                                   |   |
| Protection degree IP    | IP66/IP67          | EN 60309-4/A1 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock   |
| Protection degree IK    | IK08               |                                   |   |
| Terminals               | Screw terminals    | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Contact material        | CuZn (brass)       |                                   |   |
| Flange                  | 136X125MM_PAR      |                                   |   |

|           |                           |
|-----------|---------------------------|
| Options   | With mechanical interlock |
| Notes     | WITH FUSE HOLDER          |
| Fuse type | gG 10,3x38mm              |