



563.6387

INTERLOCKED SOCKET

63A 3P+N+E 6h 346-415V 50Hz 60Hz
136X390MM Screw terminals With mechanical interlock

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|--------------------|-----------------------------------|---|
| Product type | INTERLOCKED SOCKET | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Commercial series | ADVANCE 2 Series | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | INTERLOCKED SOCKET | | |
| Mounting version | SURFACE MOUNTING | | |
| Rated current | 63A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Poles | 3P+N+E | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Hour position | 6h | | |
| Rated voltage (range) | 250-400V | EN 60309-4 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock |
| Rated voltage | 346-415V | | |
| Working frequency | 60Hz | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 1: General requirements |
| Working frequency | 50Hz | EN 60309-2/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Colour | RED | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | EN 60309-4/A1 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock |
| Protection degree IP | IP66/IP67 | | |
| Protection degree IK | IK07 | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |

| | |
|-------------|---------------------------|
| Flange | 136X390MM |
| Cable entry | DRILLING POINT MARK |
| Options | With mechanical interlock |
| Notes | WITH FUSE HOLDER |
| Fuse type | NEOZED D02 |
| Padlock | ø5mm |