



590.EM4006

SWITCH DISCONNECTOR

40A 6P IP66/IP69 160x220x115mm Y3 IK09
EMERGENCY YELLOW/RED GW 650°C

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|---------------------|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Commercial series | ISOLATORS-TP Series | EN 60947-3 (2009) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Product type | SWITCH DISCONNECTOR | EN 60947-1 (2007) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Synthetical description | SWITCH DISCONNECTOR | EN 60947-1/A1 (2011) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Material | ENGINEERING PLASTIC | EN 60947-3/A1 (2012) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Protection degree IP | IP66/IP69 | EN 60947-1/A2 (2014) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Type | EMERGENCY | EN 60947-3/A2 (2015) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Colour | YELLOW/RED | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated current | 40A | | |
| Poles | 6P | | |
| Switch size | Y3 | | |
| Rated voltage | 690V | | |
| Dimensions | 160x220x115mm | | |
| GLOW WIRE | GW 650°C | | |
| Protection degree IK | IK09 | | |