



590.FEM31505

SWITCH DISCONNECTOR

315A 3P+N IP65 500x700x250mm FR5 IK10
EMERGENCY YELLOW/RED FIRE RATED

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|---------------------|-----------------------------------|---|
| Product type | SWITCH DISCONNECTOR | EN 60947-3 (2009) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Commercial series | ISOLATORS-FR Series | | |
| Synthetical description | SWITCH DISCONNECTOR | EN 60947-1 (2007) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Material | METAL | EN 60947-1/A1 (2011) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Protection degree IP | IP65 | | |
| Type | EMERGENCY | EN 60947-3/A1 (2012) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Colour | YELLOW/RED | | |
| Rated current | 315A | EN 60947-1/A2 (2014) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Poles | 3P+N | EN 60947-3/A2 (2015) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Switch size | FR5 | | |
| Rated voltage | 690V | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Dimensions | 500x700x250mm | | |
| Notes | FIRE RATED | | |
| Fire rated class | F400 (120min) | | |
| Protection degree IK | IK10 | | |