



590.GEB16005

SWITCH DISCONNECTOR

160A 3P+N IP55 BS 370x450x180mm KF2 IK08
GENERAL GREY/BLACK FUSE: BS GW 650°C

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|---------------------|-----------------------------------|---|
| Product type | SWITCH DISCONNECTOR | EN 60947-3 (2009) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Commercial series | ISOLATORS-TP Series | | |
| Synthetical description | SWITCH DISCONNECTOR | EN 60947-1 (2007) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Material | ENGINEERING PLASTIC | EN 60947-1/A1 (2011) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Protection degree IP | IP55 | EN 60947-3/A1 (2012) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Type | GENERAL | | |
| Colour | GREY/BLACK | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated current | 160A | | |
| Poles | 3P+N | | |
| Switch size | KF2 | | |
| Fuse type | BS | | |
| Rated voltage | 690V | | |
| Dimensions | 370x450x180mm | | |
| Notes | FUSE: BS | | |
| GLOW WIRE | GW 650°C | | |
| Protection degree IK | IK08 | | |