



## 590.GED10003

### SWITCH DISCONNECTOR

100A 3P IP55 DIN-NH 370x450x180mm KF2  
 IK09 GENERAL GREY/BLACK FUSE: DIN-NH  
 GW 650°C

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Product type	SWITCH DISCONNECTOR	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Commercial series	ISOLATORS-TP Series		
Synthetical description	SWITCH DISCONNECTOR	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	ENGINEERING PLASTIC	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Protection degree IP	IP55		
Type	GENERAL	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colour	GREY/BLACK		
Rated current	100A	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Poles	3P	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Switch size	KF2		
Fuse type	DIN-NH	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Rated voltage	690V		
Dimensions	370x450x180mm		
Notes	FUSE: DIN-NH		
GLOW WIRE	GW 650°C		
Protection degree IK	IK09		