



590.GED16003

SWITCH DISCONNECTOR

160A 3P IP55 DIN-NH 370x450x180mm KF2
 IK08 GENERAL GREY/BLACK FUSE: DIN-NH
 GW 650°C

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ISOLATORS-TP Series	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Product type	SWITCH DISCONNECTOR	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Synthetical description	SWITCH DISCONNECTOR	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	ENGINEERING PLASTIC	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Protection degree IP	IP55	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Type	GENERAL	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colour	GREY/BLACK	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Rated current	160A		
Poles	3P		
Switch size	KF2		
Fuse type	DIN-NH		
Rated voltage	690V		
Dimensions	370x450x180mm		
Notes	FUSE: DIN-NH		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		