



590.KEMB31503

SWITCH DISCONNECTOR

315A 3P IP65 BS 500x700x250mm KF4 IK10
EMERGENCY YELLOW/RED FUSE: BS

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ISOLATORS-HR Series	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Product type	SWITCH DISCONNECTOR	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Synthetical description	SWITCH DISCONNECTOR	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	METAL	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Protection degree IP	IP65	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Type	EMERGENCY	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colour	YELLOW/RED	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Rated current	315A		
Poles	3P		
Switch size	KF4		
Fuse type	BS		
Rated voltage	690V		
Dimensions	500x700x250mm		
Notes	FUSE: BS		
Protection degree IK	IK10		