



590.KGE40005-C

ENCLOSED CHANGE OVER SWITCH

400A 3P+N IP65 800x800x300mm KA3 IK10
GENERAL GREY/BLACK

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|-----------------------------|-----------------------------------|---|
| Product type | ENCLOSED CHANGE OVER SWITCH | EN 60947-3 (2009) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Commercial series | ISOLATORS-HR Series | EN 60947-1 (2007) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Synthetical description | ENCLOSED CHANGE OVER SWITCH | EN 60947-1/A1 (2011) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Material | METAL | EN 60947-3/A1 (2012) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Protection degree IP | IP65 | EN 60947-1/A2 (2014) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Type | GENERAL | EN 60947-3/A2 (2015) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Colour | GREY/BLACK | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated current | 400A | | |
| Poles | 3P+N | | |
| Switch size | KA3 | | |
| Rated voltage | 690V | | |
| Dimensions | 800x800x300mm | | |
| Protection degree IK | IK10 | | |