



590.YM80B2-C

FRONT OPERATOR PADLOCKABLE

IP65 ø22mm ø80mm C1 C2 C3 GENERAL
GREY/BLACK PER COMMUTATORE (16A-160A)

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|-------------------------------|-----------------------------------|---|
| Product type | FRONT OPERATOR PADLOCKABLE | EN 60947-3 (2009) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Commercial series | COMMAND Series | EN 60947-1 (2007) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Synthetical description | FRONT OPERATOR PADLOCKABLE | EN 60947-1/A1 (2011) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Material | THERMOPLASTIC | EN 60947-3/A1 (2012) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Protection degree IP | IP65 | EN 60947-1/A2 (2014) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Type | GENERAL | EN 60947-3/A2 (2015) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Colour | GREY/BLACK | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Switch size | C1 | | |
| Switch size | C3 | | |
| Switch size | C2 | | |
| Rated voltage | 690V | | |
| Diameter | ø22mm | | |
| Dimensions | ø80mm | | |
| Notes ¹ | PER COMMUTATORE (16A-160A) | | |