

Product Technical Sheet

24 Aug 2023 10:00



659.SC5142-36

PILLAR SMART-C - OPTIMA

4 NR IP56 580x1400x450mm

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------------|-----------------------------|-----------------------------------|--|
| Protection degree | Splash proof | IEC 61439-7 (2018) | [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations |
| Mounting version | ON TURRET | | |
| Product type | PILLAR SMART-C - OPTIMA | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Commercial series | KIOSK Series | | |
| Synthetical description | PILLAR SMART-C - OPTIMA | DIRECTIVE EMC 2014/30/UE | [European Directives] Electromagnetic Compatibility Directive |
| Material | THERMOPLASTIC | | |
| Dimensions | 580x1400x450mm | | |
| Protection degree IP | IP56 | | |
| Protection degree IK | IK10 | | |
| Inlet supply unit (*) | Supply by terminal block | | |
| No. of available outlets | 4 NR | | |
| No. of sockets 2P+E 16A (*) | 4 NR | | |
| In disp. ing/tipo apparecchio | Disconnecting switch 4P 40A | | |
| No. RCBO 2P 6A 0,03A | 4 NR | | |