



# SCM320R6W RECEPTACLE

20A 2P 3W 6h 250V 75X75MM Screw terminals

Product Approvals

| TECHDATA                   |                      | STANDARDS AND LAWS         |   |
|----------------------------|----------------------|----------------------------|---|
| Commercial series          | EUREKA-HD[UL] Series | UL 1682                    | [American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service |
| Product type               | RECEPTACLE           |                            |   |
| Synthetical description    | RECEPTACLE           |                            |   |
| Mounting version           | FLUSH MOUNTING       | IEC 60309-1 (1999)         | [International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements   |
| Rated current              | 20A                  | IEC 60309-2 (1999)         | [International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories  |
| Poles                      | 2P 3W                |                            |   |
| Hour position              | 6h                   | UL 486E                    | [American Standard] Equipment wiring terminals for use with aluinium and/or copper conductors   |
| Rated voltage (range)      | 250-400V             |                            |   |
| Rated voltage              | 250V                 | CSA C22.2 No. 182.1 (1988) | [Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products   |
| Colour                     | BLUE                 |                            |   |
| Material                   | THERMOPLASTIC        | CSA C22.2 No. 65-93        | [Canadian Standard] Wire connectors wiring products   |
| Protection degree          | Watertight           |                            |   |
| Protection degree IP       | IP67                 |                            |   |
| Protection degree IK       | IK10                 |                            |   |
| Types of available outlets | STRAIGHT             |                            |   |
| Terminals                  | Screw terminals      |                            |   |
| Contact material           | CuZn (brass)         |                            |   |
| Flange                     | 75X75MM              |                            |   |