

Product Technical Sheet

24 Aug 2023 16:57



SCM330C4W CONNECTOR

30A 2P 3W 4h 125V Screw terminals



Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	EUREKA-HD[UL] Series	UL 1682	[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
Product type	CONNECTOR		
Synthetical description	CONNECTOR		
Mounting version	PORTABLE	IEC 60309-1 (1999)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Rated current	30A	IEC 60309-2 (1999)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories
Poles	2P 3W		
Hour position	4h	UL 486E	[American Standard] Equipment wiring terminals for use with aluinium and/or copper conductors
Rated voltage (range)	50-200V		
Rated voltage	125V	CSA C22.2 No. 182.1 (1988)	[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
Colour	YELLOW		
Material	THERMOPLASTIC	CSA C22.2 No. 65-93	[Canadian Standard] Wire connectors wiring products
Protection degree	Watertight		
Protection degree IP	IP67		
Protection degree IK	IK10		
Types of available outlets	STRAIGHT		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Cable entry	CABLE GLAND		