

Product Technical Sheet

24 Aug 2023 17:36



SCM430C7S CONNECTOR

30A 3P 4W 7h 3Ø480V Screw terminals



Product Approvals

TECHDATA		STANDARDS AND LAWS	
Product type	CONNECTOR	UL 1682	[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
Commercial series	EUREKA-HD[UL] Series		
Synthetical description	CONNECTOR		
Mounting version	PORTABLE	IEC 60309-1 (1999)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Rated current	30A	IEC 60309-2 (1999)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories
Poles	3P 4W		
Hour position	7h	UL 486E	[American Standard] Equipment wiring terminals for use with aluinium and/or copper conductors
Rated voltage (range)	400V-up		
Rated voltage	3Ø480V	CSA C22.2 No. 182.1 (1988)	[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
Colour	RED		
Material	THERMOPLASTIC	CSA C22.2 No. 65-93	[Canadian Standard] Wire connectors wiring products
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK10		
Types of available outlets	STRAIGHT		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Cable entry	CABLE SLEEVE		