



# SCM530MI7W-NB

## INTERLOCKED SOCKET

30A 4P 5W 7h 3ØY277/480V 130X260MM

Screw terminals With mechanical interlock

### Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ADVANCE-GRP[UL] Series	UL 508	[American Standard] Industrial Control Equipment
Product type	INTERLOCKED SOCKET	IEC 60309-1 (2012)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 1: General requirements
Synthetical description	INTERLOCKED SOCKET	IEC 60309-2 (2012)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories
Rated current	30A	IEC 60309-4 (2012)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 4: Switched socket-outlets and connectors with or without interlock
Poles	4P 5W	UL 60947-1	[American Standard] Low-Voltage Switchgear and Controlgear - Part 1: General rules
Hour position	7h	UL 60947-4-1	[American Standard] Low-Voltage Switchgear and Controlgear - Part 4-1: Contactors and Motor-Starters - Electromechanical Contactors and Motor-Starters
Rated voltage (range)	250-400V	CSA C22.2 No. 60947-1-13	[Canadian Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Rated voltage	3ØY277/480V	CSA C22.2 No. 60947-4-1-14	[Canadian Standard] Low-voltage switchgear and controlgear - Part 4-1: Contactors and motor-starters - Electromechanical contactors and motor-starters
Colour	RED	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Material	GRP Glass Reinforced Polyester		
Protection degree	Watertight		
Protection degree IP	IP66/IP67/IP69		
Protection degree IK	IK10		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Flange	130X260MM		
Working temperature	-40°C/+60°C		
GLOW WIRE	GW 960°C		

Self-extinguishing UL94	V0
Options	With mechanical interlock
Notes	WITHOUT BASE
Padlock	ø5mm