



SCM563B6W

FLUSH MOUNTING APPLIANCE INLET

63A 4P 5W 6h 346-415V 50/60Hz 120X120MM
Screw terminals

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|----------------------------|-----------------------------------|---|---|
| Product type | FLUSH MOUNTING APPLIANCE INLET | IEC 60309-1 (1999) | [International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Commercial series | EUREKA-HD[UL] Series | IEC 60309-2 (1999) | [International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories |
| Synthetical description | FLUSH MOUNTING APPLIANCE INLET | | |
| Mounting version | FLUSH MOUNTING | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated current | 63A | | |
| Poles | 4P 5W | | |
| Hour position | 6h | | |
| Rated voltage (range) | 250-400V | | |
| Rated voltage | 346-415V | | |
| Working frequency | 50/60Hz | | |
| Colour | RED | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP67 | | |
| Protection degree IK | IK10 | | |
| Types of available outlets | 90° ANGLED | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |

| | |
|----------------------------|---------------|
| Surface treatment contacts | Nickel-plated |
| Flange | 120X120MM |