

## 204.UB11M-UN

Plastic wall mounting consumer unit with  
2 domestic interlocked German sockets type  
16A 230Vac 3,7kW



### > REFERENCE STANDARD

#### EN 61439-3

Low-voltage switchgear and controlgear assemblies  
Part 3: Distribution boards intended to be operated  
by ordinary persons

### > TECHNICAL CHARACTERISTICS

Rated current:	<b>32A</b>
Rated voltage:	<b>230Vac</b>
Frequency:	<b>50-60Hz</b>
Insulating voltage:	<b>250V</b>
Protection degree:	<b>IP56</b>
Operating temperature:	<b>-25°C +40°C</b>
Material:	<b>Engineering plastic</b>
Glow wire test:	<b>650°C</b>
IK degree at 20°C:	<b>IK07</b>
Color:	<b>Anthracite</b>
Mounting:	<b>Wall mounting</b>
Salt mist:	<b>Resistant</b>
UV radiation:	<b>Resistant</b>

### > FUNCTIONS

charge in mode 1  
protection against overcurrents and electric shock  
protection against direct contact Safety Child Shutters  
working in mode stand-alone free

### > EQUIPMENTS

2 RCD 2P 25A 30mA ist. AC  
2 MCB 1P+N C16 4,5 KA  
2 interlocked IP56 sockets mated

### > DIMENSION

