

204.WD26P-T2T2


Wall mounting box in plastic and painted steel with 2 sockets Type 2 16A 400Vac 11kW with plug/lid lock



> FUNCTIONS

charge in mode 3 with pwm circuit pilot
 identification of connected cord-set size
 charge managing in case of power outage
 protection against overcurrents and electric shock
 protection against direct contact Safety Child Shutters
 current consumption metering
 managing of lid locking and latching system
 working in mode stand-alone free
 predisposition for serial communication

> DIMENSION



> REFERENCE STANDARD

IEC/EN 61851-1

Electric vehicle conductive charging system.
 Part 1: General requirement.

IEC/EN 61439-7

Low-voltage switchgear and control gear assemblies.
 Part 7: Assemblies for e.v. charging stations.

> TECHNICAL CHARACTERISTICS

Rated current:	32A
Rated voltage:	400Vac
Frequency:	50-60Hz
Insulating voltage:	500V
Protection degree:	IP54
Operating temperature:	-30°C +50°C
Material:	Engineering plastic
Glow wire test:	650°C
IK degree at 20°C:	IK10
Color:	Grey
Mounting:	Wall mounting
Salt mist:	Resistant
UV radiation:	Resistant

> EQUIPMENTS

2 lighting bars with RGB led
 1 terminal strip 1x35mm²
 1 main switch 4P 40A
 2 circuit breakers 3P+N C25 30mA ist. A
 2 current transformers
 2 modular contactors 4P 20A 24Vdc
 2 DC Leakage detectors
 1 fuse holder 1P+N gG 4A
 1 power supply 24Vdc 36W
 2 control cards
 2 lcd display 2x20 rows backlight
 2 stop charge push-buttons (mode free)
 1 backup battery