

## 205.KC09-K

Pillar in painted metal with  
2 sockets P40 16A 230Vac 3,7kW



### > FUNCTIONS

protection against overcurrents and electric shock  
protection against direct contact Safety Child Shutters  
manual door closing management  
working in mode stand-alone free

### > NORME DI RIFERIMENTO

#### EN 61439-3

Low-voltage switchgear and controlgear assemblies  
Part 3: Distribution boards intended to be operated  
by ordinary persons

### > TECHNICAL CHARACTERISTICS

Rated current:	<b>16A</b>
Rated voltage:	<b>230Vac</b>
Frequency:	<b>50-60Hz</b>
Insulating voltage:	<b>250V</b>
Protection degree:	<b>IP44</b>
Operating temperature:	<b>-30°C +50°C</b>
Material:	<b>Pillar in painted metal</b>
Glow wire test:	-
IK degree at 20°C:	<b>IK10</b>
Color:	<b>Bronze</b>
Mounting:	<b>Base</b>
Salt mist:	<b>Resistant</b>
UV radiation:	<b>Resistant</b>

### > EQUIPMENTS

1 base with separation chamber  
1 terminal strip 3x10mm<sup>2</sup>  
1 circuit breaker 1P+N D20 30mA ist. A  
1 modular contactor 2P 25A 24Vdc  
1 fuse holder 1P+N gG 4A  
1 power supply 24Vdc 36W

### > DIMENSIONI

