Product Technical Sheet

23 Aug 2023 01:32





240.1697-7

SURFACE MOUNT. APPLIANCE INLET

16A 6P+E 6h 380-415V 50Hz 60Hz Screw terminals

Product Approvals

| TECHDATA | | STANDARDS | AND LAWS |
|----------------------------|-----------------------------------|-------------------------|--|
| Product type | SURFACE MOUNT. APPLIANCE INLET | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Commercial series | OPTIMA-SEVEN Series | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part |
| Synthetical description | SURFACE MOUNT. APPLIANCE INLET | EN 60309-1/A2 (2012) | 1: General requirements [European Standard] Plugs, socket-outlets and couplers for industrial purposes Part |
| Mounting version | SURFACE MOUNTING | DIRECTIVE LOW | General requirements [European Directives] Low Voltage |
| Rated current | 16A | VOLTAGE 2014/35 /UE | Directive Directives |
| Poles | 6P+E | | |
| Hour position | 6h | | |
| Rated voltage (range) | 250-400V | | |
| Rated voltage | 380-415V | | |
| Working frequency | 50Hz | | |
| Working frequency | 60Hz | | |
| Colour | RED | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Splash proof | | |
| Protection degree IP | IP44 | | |
| Protection degree IK | IK08 | | |
| Types of available outlets | ANGLED | | |
| Terminals | Screw terminals | | |

| Contact material | CuZn (brass) | |
|----------------------------|---------------|--|
| Surface treatment contacts | Nickel-plated | |
| Cable entry | M25X1,5 | |