



## 423.6366.K

# FLUSH-MOUNTING SOCKET

63A 3P+E 6h 380-415V 50Hz 60Hz

100X110MM Mantle terminals

Product Approvals

| TECHDATA                   |                       | STANDARDS AND LAWS                |   |
|----------------------------|-----------------------|-----------------------------------|---|
| Commercial series          | OPTIMA Series         | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Product type               | FLUSH-MOUNTING SOCKET | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations   |
| Synthetical description    | FLUSH-MOUNTING SOCKET |                                   |   |
| Mounting version           | FLUSH MOUNTING        | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Rated current              | 63A                   | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations   |
| Poles                      | 3P+E                  |                                   |   |
| Hour position              | 6h                    |                                   |   |
| Rated voltage (range)      | 250-400V              | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 1: General requirements  |
| Rated voltage              | 380-415V              | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Working frequency          | 60Hz                  |                                   |   |
| Working frequency          | 50Hz                  |                                   |   |
| Colour                     | RED                   | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Material                   | THERMOPLASTIC         | DIRECTIVE RoHS 2011/65/EU         | [European Law] Restriction of the use of certain hazardous substances in electrical and electronic equipment  |
| Protection degree          | Splash proof          |                                   |   |
| Protection degree IP       | IP44/IP54             |                                   |   |
| Protection degree IK       | IK08                  |                                   |   |
| Types of available outlets | STRAIGHT              |                                   |   |
| Terminals                  | Mantle terminals      |                                   |   |

|                  |                |
|------------------|----------------|
| Contact material | CuZn (brass)   |
| Flange           | 100X110MM      |
| Notes            | BLACK COLOURED |