



504.16862-A

INTERLOCKED SOCKET

16A 3P+E 2h >50V >300-500Hz II 2GD
130X260MM_PAR Screw terminals With
mechanical interlock Low temperature [-50°C]

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|--------------------------------|---------------------------|---|
| Product type | INTERLOCKED SOCKET | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Commercial series | ADVANCE-GRP[GD] Series | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | INTERLOCKED SOCKET | | |
| Mounting version | SURFACE MOUNTING | | |
| Rated current | 16A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Poles | 3P+E | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 1: General requirements |
| Hour position | 2h | EN 60079-1 (2014) | [European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd' |
| Rated voltage (range) | 50-200V | | |
| Rated voltage | >50V | EN 60079-7 (2015) | [European Standard] Explosive atmospheres. Equipment protection by increased safety "e" |
| Working frequency | >300-500Hz | EN 60079-7 (2018) | [European Standard] Explosive atmospheres. - Part 7: Equipment protection by increased safety "e" |
| Colour | RED | | |
| Material | GRP Glass Reinforced Polyester | EN 60079-0 (2018) | [European Standard] Explosive atmospheres. General requirements. |
| Protection degree | Splash proof | DIRECTIVE ATEX 2014/34/UE | [European Directives] Atmosphere Explosive |
| Protection degree IP | IP66 | | |
| Protection degree IK | IK10 | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |
| Flange | 130X260MM_PAR | | |

| | |
|----------------------------|---------------------------|
| Cable entry | 1xM25 |
| Working temperature | -40°C/+60°C |
| GLOW WIRE | GW 960°C |
| Self-extinguishing UL94 | V0 |
| Group and categories EX | II 2GD |
| Ambient temperature Ta min | -50 °C |
| Ambient temperature Ta max | 60 °C |
| Options | With mechanical interlock |
| Options | Low temperature [-50°C] |
| Padlock | ø5mm |