

Product Technical Sheet

23 Aug 2023 13:02



504.16875-A.RU

INTERLOCKED SOCKET

16A 3P+N+E 11h 440-460V 60Hz II 2GD
130X260MM_PAR Screw terminals With
mechanical interlock EAC [Eurasian Conformity]
Low temperature [-50°C]

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ADVANCE-GRP[GD] Series	31610.0-2014 (IEC [] . 60079-0)	
Product type	INTERLOCKED SOCKET	DIRECTIVE ATEX [European Directives] Atmosphere 2014/34/UE Explosive	
Synthetical description	INTERLOCKED SOCKET		
Mounting version	SURFACE MOUNTING		
Rated current	16A		
Poles	3P+N+E		
Hour position	11h		
Rated voltage (range)	400V-up		
Rated voltage	440-460V		
Working frequency	60Hz		
Colour	RED		
Material	GRP Glass Reinforced Polyester		
Protection degree	Splash proof		
Protection degree IP	IP66		
Protection degree IK	IK10		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Flange	130X260MM_PAR		

Cable entry	1xM25
Working temperature	-40°C/+60°C
GLOW WIRE	GW 960°C
Self-extinguishing UL94	V0
Group and categories EX	II 2GD
Ambient temperature Ta min	-50 °C
Ambient temperature Ta max	60 °C
Options	Low temperature [-50°C]
Options	EAC [Eurasian Conformity]
Options	With mechanical interlock
Padlock	ø5mm