



504.3287-A.RU

INTERLOCKED SOCKET

32A 3P+N+E 6h 346-415V 50Hz 60Hz II 2GD
 130X260MM_PAR Screw terminals With
 mechanical interlock EAC [Eurasian Conformity]
 Low temperature [-50°C]

Product Approvals

| TECHDATA | | STANDARDS AND LAWS |
|-------------------------|--------------------------------|-------------------------------------|
| Commercial series | ADVANCE-GRP[GD] Series | 31610.0-2014 (IEC [] . 60079-0) |
| Product type | INTERLOCKED SOCKET | |
| Synthetical description | INTERLOCKED SOCKET | |
| Mounting version | SURFACE MOUNTING | |
| Rated current | 32A | |
| Poles | 3P+N+E | |
| Hour position | 6h | |
| Rated voltage (range) | 250-400V | |
| Rated voltage | 346-415V | |
| Working frequency | 50Hz | |
| Working frequency | 60Hz | |
| Colour | RED | |
| Material | GRP Glass Reinforced Polyester | |
| Protection degree | Splash proof | |
| Protection degree IP | IP66 | |
| Protection degree IK | IK10 | |
| Terminals | Screw terminals | |
| Contact material | CuZn (brass) | |

| | |
|----------------------------|---------------------------|
| Flange | 130X260MM_PAR |
| Cable entry | 1xM32 |
| Working temperature | -40°C/+60°C |
| GLOW WIRE | GW 960°C |
| Self-extinguishing UL94 | V0 |
| Group and categories EX | II 2GD |
| Ambient temperature Ta min | -50 °C |
| Ambient temperature Ta max | 60 °C |
| Options | EAC [Eurasian Conformity] |
| Options | Low temperature [-50°C] |
| Options | With mechanical interlock |
| Padlock | ø5mm |