



ENCLOSED SWITCH-DISCONNECTORS HIGH WIRING CAPACITY

20÷80A

2P-3P-3P+N



20÷40A

2P-3P-3P+N



63÷80A

2P-3P-3P+N



InfoTECH

ITALY

WORLDWIDE


Numero Verde


800-018009

ScameOnLine

www.scame.com

infotech@scame.com

		20÷40A 2P-3P-3P+N	63÷80A 2P-3P-3P+N
Wire range		1.5÷10mm ²	10-35mm ²
Tightening torque	Terminal screws	0.8Nm	3.6Nm
	Fixing screws	1.2Nm	1.2Nm
Wire strip length		10mm	13mm




ATTENTION

When mounting or removing additional elements the switch **has to be in OFF position** for avoiding damages to mechanism.


When removing main switch following instruction for avoiding damages.

THERMOPLASTIC ENCLOSURES

20÷80A
2P-3P-3P+N



63-80A
2P-3P-3P+N








Cable entries





Top	/	Blank side
Bottom	/	Blank side
Rear	/	Blank side

ALUMINIUM ENCLOSURES

20÷40A
2P-3P-3P+N



63-80A
2P-3P-3P+N



Cable entries		
Top	/	Blank side
Bottom	/	Blank side
Rear	/	Blank side