



# 590.SEM12505.SN

## SWITCH DISCONNECTOR

125A 3P+SN IP65 300x400x150mm Y5 IK10  
EMERGENCY YELLOW/RED SN (SOLID NEUTRAL)

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Product type	SWITCH DISCONNECTOR	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Commercial series	ISOLATORS-INOX Series		
Synthetical description	SWITCH DISCONNECTOR	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	STAINLESS STEEL [AISI304L]	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Protection degree IP	IP65	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Type	EMERGENCY		
Colour	YELLOW/RED	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Rated current	125A		
Poles	3P+SN	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Switch size	Y5		
Rated voltage	690V	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Dimensions	300x400x150mm		
Notes	SN (SOLID NEUTRAL)		
Protection degree IK	IK10		